


# FLT-LLOI

## LTE Cat M 1/NB2 GNSS Asset Tracker

With low power consumption and optimized data transmission, FLT-LLOI series allows you to track and locate any asset. The internal 10,000 battery enables an incredible battery life of up to 3 years. Tamper detection allows you to be notified should the device be removed from the asset, giving you peace of mind that your assets are protected. You can install them on all of your assets with the convenient magnetic design.



- LTE Cat M1/NB2 & GSM**
- 10,000 Battery Powered**
- Tamper Alert**
- IP65 Dust & Water Resistance**
- 3 Years Standby Time**
- Strong Magnet Mount**



### Market Applications



Parameters	
Operating band	IIE Cat-M1/NB2: B2/B4/B5/B12/B13/B66 (JM-LLOIA) IIE Cat-M1 /NB2: B1 /B3/B5/B8/B20 (JM-LLOI E) EGPRS: 850/ 1900MHz 900/ 1800MHz (JM-LLOI E)
Data transmission	IIE Cat M1: Max. 588kbps (DL), Max. 1.119Mbps (UL) IIE Cat NB2: Max. 127kbps (DL), Max. 158.5kbps (UL) EGPRS: Max. 296kbps (DL), Max. 236.Bkbps(UL)
Cellular antenna	Internal only
GNSS antenna	Internal patch antenna
LED indicators	CELPWR
Mini USB interface	Used for charging and debugging
Battery	10000 mAh, 3.7V Li-Polymer battery
Operating temperature	-20 °C~+70 °C
Device dimension	109*61 *30.5 mm